





Appearance Parameters

Model	Dimension (mm)			Product Size (mm)	Cut out (mm)	Net Weight (kg)
	A	B	C			
UP-CL59-2	Ø80	Ø60	39	Ø80x39	Ø60-70	0.28
UP-CL59-2.5	Ø85	Ø66	39.5	Ø85x39.5	Ø70-75	0.3
UP-CL59-3	Ø110	Ø90	38	Ø110x38	Ø90-100	0.4
UP-CL59-4	Ø145	Ø114	45	Ø145x45	Ø120-130	0.59



Model	Dimension (mm)			Product Size (mm)	Cut out (mm)	Net Weight (kg)
	A	B	C			
UP-CL59-5	Ø170	Ø134	45	Ø170x45	Ø140-150	0.7
UP-CL59-6	Ø190	Ø153	45	Ø190x45	Ø160-170	0.83
UP-CL59-8	Ø228	Ø192	45	Ø228x45	Ø200-210	1.1
UP-CL59-10	Ø280	Ø229	52	Ø280x52	Ø230-260	1.7



Downlight CL59 2" / 2.5" / 3" / 4" / 5" / 6" / 8" / 10"



Introduction

- Up-shine SMD LED Down light adopts high lumen SMD LED, PMMA diffuser with even light output.
- White, silver, chrome surface treatment available for different applications.
- Triac dimmable, 0-10V dimmable and DALI dimmable version shares great popularity by the excellent dimming effect.
- Application: Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.

Technical Specifications

Voltage: AC100-240V / AC200-240V
 Power: 7W / 10W / 13W / 18W / 25W / 35W / 45W
 Power Factor: ≥0.9
 Beam angle: 90°
 CCT: 3000K 4000K 5000K 5700K

Lifespan: 40000hrs
 CRI: ≥80
 IP: 20 / 44
 Dimmable: Triac / 0-10V dimmable
 Surface color: White / Silver

Model	Non-DIM Lumen (±5%)				DIM Lumen (±5%)			
	3000K	4000K	5000K	5700K	3000K	4000K	5000K	5700K
UP-CL59-2-7W	430	450	460	480	400	420	440	460
UP-CL59-2.5-10W	685	700	720	730	640	660	700	710
UP-CL59-3-10W	685	700	720	730	640	660	700	710
UP-CL59-3-13W	850	880	900	950	800	830	860	900
UP-CL59-4-13W	850	880	900	950	800	830	860	900
UP-CL59-4-18W	1320	1360	1420	1450	1300	1340	1390	1420
UP-CL59-5-18W	1400	1430	1490	1550	1380	1410	1450	1480
UP-CL59-5-25W	1850	1900	2000	2100	1800	1850	1920	2000
UP-CL59-6-18W	1430	1460	1500	1560	1390	1430	1480	1510
UP-CL59-6-25W	1930	1990	2060	2130	1880	1950	2000	2070
UP-CL59-6-35W	2600	2680	2760	2830	2570	2630	2710	2760
UP-CL59-8-18W	1390	1430	1490	1540	1360	1390	1420	1480
UP-CL59-8-25W	1900	1960	2060	2130	1850	1910	2020	2100
UP-CL59-8-35W	2590	2640	2700	2790	2560	2410	2680	2750
UP-CL59-10-45W	3600	3780	4000	4050	3460	3680	3870	3900